

THE NEW Steadicam Scout



- Standard composite BNC video input connector and RCA output connector
- Standard 3-pin LEMO power in/out connectors on the base and stage
- Standard 7" LCD and choice of Anton Bauer or V-lock battery mounts

Sled Base:

- Rigid aluminum monitor/battery rod easily adjusts for quick set-ups and is easily removable for compact storage or transport
- Single knob rod release for quick set-ups
- Independently adjustable battery and monitor mounts for dynamic balance adjustability
- Tilting and rotationally indexed monitor mount
- Inertial control and adjustability via standard Steadicam Merlin type balance weights
- Balance control via standard 1/4-20 mounting hole at the base of the sled and additional balance weights
- Anton Bauer or V-lock battery compatible
- Telescopic, indexed carbon fiber main post with internal safety line
- Standard 7" composite LCD
- No tools post clamp

Gimbal:

- Knurled gimbal grip with ergonomic handle

Stage:

- Rigid low profile aluminum frame XY vernier stage
- Drop in standard dovetail plate design with fore-aft safety stops



INNOVATION STARTS AT TIFFEN.
THE TIFFEN COMPANY
90 OSER AVENUE
HAUPPAUGE, NY 11788
1.800.645.2522 • 631.273.2500
SEE OUR FULL RANGE OF PRODUCTS
AT WWW.TIFFEN.COM

STEADICAMTM SCOUTTM

Explore the Possibilities



STYLE ON THE FLY

A combination of innovative features

The Steadicam® Scout™ incorporates the same revolutionary Steadicam features that won the coveted DV Professional Association's "Best of Show" at NAB.

"Style, functionality, flexibility and affordability" all wrapped within the new Steadicam Scout™.

A combination of innovative features derived from our popular PILOT™, FLYER™, ZEPHYR™ and ARCHER² Steadicam systems now allows it to "Excel in the range of operating possibilities," said Frank Rush, VP, General Manager of Steadicam.

A new innovative approach to camera stabilizer design, the Steadicam Scout™ has uncompromising quality and all the necessary features to get the job done at an affordable price.

- 5-18 lb. (2.3 - 8kg) camera payload capacity.
- No-tools adjustable Iso-Elastic™ arm
- Dual axis vernier adjustable stage
- Unparalleled inertial control and dynamically adjustable base



Scout base shown with V-lock battery mount and balance weights.

The Scout™ vest is a continuation of the comfortable Flyer™ vest. An ergonomic fit of the breast plate combined with solid metal shoulder fasteners assure a new comfort level for extended use and a secure fit. New vest and pad covers are easily removed for cleaning or replacement offering extended durability.

The new tools-free patented Iso-Elastic™ stabilizer arm supports 18 pounds (8kg) of camera weight. The no-tools Arm/Vest interface allows for quick customization to the individual operator. "On the fly" weight adjustment frees the operator from dismantling the system to make changes.

The open design of the arm has freedom of movement unknown in this weight class and the Scout's adjustable and interchangeable arm post assembly is a feature usually found on more expensive systems. The 2-section arm can also be separated for compact storage and transport.



Dynamically adjustable Scout base showing quick release rod and post clamp.

The new 7" Scout™ Steadicam color LCD monitor features enhanced image quality and a wide viewing angle. Even under bright sunlight this monitor is ideal for field production use.

The Scout™ light weight aluminum dovetail stage was designed for camera mounting stability.



Stage rear showing LEMO power connector and BNC video input connector.



Stage front showing standard drop in dovetail mount with safety stop.

An innovative approach